

# United States Patent [19]

Nakayama et al.

[11] Patent Number: 5,023,799

[45] Date of Patent: Jun. 11, 1991

## [54] VEHICULAR TRAVELING DIRECTION MEASURING SYSTEM

[75] Inventors: Okihiko Nakayama; Hiroshi Tsuda; Toshiyuki Itoh; Hiroshi Ueno, all of Kanagawa, Japan

[73] Assignee: Nissan Motor Company, Limited, Japan

[21] Appl. No.: 474,922

[22] Filed: Feb. 6, 1990

### [30] Foreign Application Priority Data

Feb. 6, 1989 [JP] Japan ..... 1-27059

[51] Int. Cl.<sup>3</sup> ..... G01C 17/38

[52] U.S. Cl. .... 364/449; 364/454; 364/457; 364/571.05; 33/356

[58] Field of Search ..... 364/443, 449, 453, 454, 364/457, 571.05; 33/356, 357, 355 R; 73/178 R

### [56] References Cited

#### U.S. PATENT DOCUMENTS

4,672,565 6/1987 Kuno et al. .... 33/357  
4,673,878 6/1987 Tsushima et al. .... 364/449  
4,771,547 9/1988 Akutsu et al. .... 33/356  
4,791,574 12/1988 Thoone et al. .... 364/457  
4,831,563 5/1989 Ando et al. .... 33/356  
4,841,449 6/1989 Suyama ..... 364/449  
4,862,398 8/1989 Shimizu et al. .... 33/356  
4,890,233 12/1989 Ando et al. .... 364/457

## FOREIGN PATENT DOCUMENTS

59-100812 6/1984 Japan .  
64-46612 2/1989 Japan .  
1-117712 8/1989 Japan .  
1-144814 10/1989 Japan .

Primary Examiner—Gary Chin  
Attorney, Agent, or Firm—Lowe, Price, LeBlanc, Becker & Shur

## [57] ABSTRACT

A system measures a traveling direction of a vehicle based on a direction toward a coordinate position defined by outputs of a geomagnetic sensor from a first coordinate position of a center of a corresponding output circle. The system utilizes a preliminary coordinate position as a preliminarily corrected value of the first coordinate position, a first value indicative of accuracy of the preliminary coordinate position and a second value which is variable depending on a variation in a magnetization level on a vehicle body. The system derives a finally corrected value of the first coordinate position based on the preliminary coordinate position and a latest value of the finally corrected value which has been derived in a prior execution of the system, by changing a rate which determines a point of the current finally corrected value between the latest finally corrected value and the preliminary coordinate position.

22 Claims, 16 Drawing Sheets

